



Shade SELECTION



KAMOSTAR

PERFORMANCE QUALITY
EXTERIOR PAINT



KAMOCEM

EMULSION

FOR EXTERIOR & INTERIOR WALLS



KAMOSTAR EMULSION

Popular Exterior Vibrant Shades



PASSION YELLOW

KS 0067



MATRIX GREEN

KS 0065



GOLDEN GLOW

KS 0068



FANTASY GREEN

KS 0066



PAPAYA YELLOW

KS 0069



LAPIS LAZULI

KS 0078



VIBRANT ORANGE

KS 0073



ROYAL BLUE

KS 0020



BOUGAINVILLEA

KS 0070



MING RED

KS 0042



NUT BROWN

KS 0040



TERRACOTTA

KS 0061

Shades are shown for indication purpose only.

KAMOCEM EMULSION

Popular Cement Paint Shades



IVORY

KC 0005



NEW PALE ROSE

KC 0020



MIDCREAM

KC 0008



PEACH

KC 0016



LIGHT BISCUIT

KC 0012



AQUAMARINE

KC 0028



DHOLPUR STONE

KC 0015



APPLE GREEN

KC 0035



PINK

KC 0021



TERRACOTA

KC 0022



CANDY PINK

KC 0018



GOLDEN BROWN

KC 0036

Shades are shown for indication purpose only.

KAMOSTAR

PERFORMANCE QUALITY
EXTERIOR PAINT



**ECONOMICAL EXTERIOR
EMULSION**

**SUITABLE FOR DRY
& HUMID CLIMATE**

Available in 20 ltr, 10 ltr, 4 ltr & 1 ltr.



KAMOCEM

EMULSION
FOR EXTERIOR & INTERIOR WALLS



- **ECONOMICAL DUAL EMULSION**
- **EMULSION FINISH ON COST OF CEMENT PAINT**
- **NO CURING IS REQUIRED**
- **SAVE WATER - SAVE EARTH**

Available in 10 kg. & 5 kg.

RECOMMENDED PAINTING SYSTEM

- ▶ **How to Prepare the Surface:** Clean the surface with a wire brush to remove loose paint, dust, grease, algae and fungus. After that, wash the surface down with Kamo Biowash to prevent reoccurrence of microbiological growth.
- ▶ **Smoothering the Surface:** Kamocare/ Kamoplast wall putty is recommended for leveling & smoothering the surface. It is effective in removing holes, dents, cracks and minor undulations. Larger cracks may be filled with a mixture of white cement and sand in the ration of 1:3.
- ▶ **Priming:** If the surface is highly absorbent, then, once Kamocare/ Kamoplast wall putty is to be applied, you may use Kamo Exterior Sealer. In the case of a fresh surface or repainting surfaces, apply one coat of Kamoprime Exterior Primer in the ration of 1:1.
- ▶ **Top Coat :** Apply 2 to 3 coats of Kamostar by diluting 1 litre of Paint with 500 to 600 ml of water. Or apply 2 to 3 coats of Kamocem by diluting 1 kg of Paint with 450 ml to 500 ml of water. Keep an interval of 4 to 6 hours between the two coats. An additional coat is required for dark shades and hozizontal surface like window tops & ledges, etc.

PRECAUTION

- 01 For freshly plastered surfaces three months are required for curing before the painting of the walls.
- 02 For highly absorbent and chalky surfaces Kamo Exterior Sealer is recommended.
- 03 Paint procedure should not be applied on continuous seeping & damp surface.
- 04 Use of Kamdhenu Exterior Primer is mandatory for all exterior paint surfaces.
- 05 Use Kamdhenu Waterproofing System before painting on the seepage and damp surfaces.



LOW VOC



LEAD FREE



ECO-FRIENDLY

**Dreamz
Colour**
Dil Ke Rang Deewaron Pe

KAMDHENU LIMITED

2nd Floor, Building No. 9A, DLF Cyber City, Phase-III, Gurugram (HR.)-122002

Fax: 0124-4218524, Email: kamdhenu@kamdhenulimited.com

+91-124-4604500 (30 Lines) Toll Free: 1800 1800 545



www.kamdhenupaints.com